

UNIGATE® CX

Connecting incompatible networks

- Easy installation
- Norm compliant
- Certified
- Ready-to-use
- Configurable
- Programmable
- Designed & manufactured in Germany



Data sheet

EtherNet/IP

EtherNet/IP I/O adapter (Slave)

100 Mbit/s full duplex

Isolated EtherNet/IP interface with 2x RJ45 connector

Integrated 2 port switch (e. g. for daisy chaining)

Generic EDS file (by configuration)

Up to 1060 Bytes input- and 1060 Bytes output data

Modbus TCP

Complete Modbus TCP interface

10/100 Mbit/s

Isolated Fast Ethernet interface 1x RJ45 connector

IT functions: Web server, FTP server

Up to 252 Bytes Input- and 252 Bytes output data

Technical data

Dimensions (WxDxH in mm)	46 x 117 x 100 (incl. screw-plug-connector) 46 x 117 x 106 (without screw-plug-connector)
Weight	247 g
Mounting	DINrail (EN 50022)
Operating voltage	10 up to 33 Volt DC Protection against incorrect polarity, short circuit and overload integrated
Current consumption (at +24V/DC)	typ. 182mA, max. 232mA
Operating temperature	-25°C (non condensing) up to +85°C
Storage-/Transport temperature	-40°C ... +85°C
Fieldbus functions	All specified EtherNet/IP Slave functions UDP, TCP/IP, Modbus TCP, E-mail, Web server
Technology	ASIC
Certificates	CE