

UNIGATE[®] CX

Connecting incompatible networks

Easy installation
Norm compliant
Certified
Ready-to-use

Configurable
Programmable
Designed & manufactured in Germany



Data sheet

Ethernet TCP/IP

Complete Fast Ethernet interface

10/100 Mbit/s

Isolated Fast Ethernet interface with 2x RJ45 connection

IT Functions: Web server, FTP server

Up to 1024 Bytes input- and 1024 Bytes output data

DeviceNet

Complete DeviceNet Slave interface

125, 250 and 500 kbit/s adjustable

DeviceNet functions: I/O Slave messaging, Polling

Isolated DeviceNet-interface with 5-pin. terminal connection

Generic EDS file (by configuration)

Up to 255 Bytes input- and 255 Bytes output data

Technical data

Dimensions (WxDxH in mm)	46 x 117 x 100 (incl. screw-plug-connector) 46 x 117 x 106 (without screw-plug-connector)
Weight	237 g
Mounting	DINrail (EN 50022)
Supply voltage	10 up to 33 Volt DC Protection against incorrect polarity, short circuit and overload integrated
Current consumption (at +24V/DC)	typ. 97mA, max. 117mA
Operating temperature	-25°C (non condensing) up to +85°C
Storage-/Transport temperature	-40°C ... +85°C
Fieldbus functions	UDP, TCP/IP, Modbus TCP, e-mail, web server All specified DeviceNet Slave Functions
Technology	ASIC
Certificates	CE